



CDN 500 ISO 7637-3 CAPACITIVE COUPLING CLAMP



- Precision transient capacitive coupler
- Complies with ISO 7637-3
- High quality brass plated surfaces

The coupling clamp CDN 500 is manufactured exactly in accordance with the drawings and specifications of ISO 7637-3 for capacitively coupling the transients onto cables and wiring harnesses. With its characteristic impedance of 50Ω , the CDN 500 coupling clamp is connected to the generator via a coaxial cable and terminated on the far side with a 50Ω load resistor. A suitable terminating load is available as an accessory under the type number INA 5030, which also provides a measurement output via a 40 dB attenuator. The coupling clamp will accept ribbon cables as well as round cables of up to 40 mm diameter. The effective coupling capacitance depends on the cross section and the material of the cable used; a typical value being around 100 pF.

For more details, see the complete catalog "Automotive Electrical Disturbances".

Teseq AG
Nordstrasse 11F 4542 Luterbach Switzerland
T +41 32 681 40 40 F +41 32 681 40 48
sales@teseq.com www.teseq.com

© February 2011 Teseq®
Specifications subject to change without notice.
Teseq® is an ISO-registered company. Its products are designed and manufactured under the strict quality and environmental requirements of the ISO 9001. This document has been carefully checked. However, Teseq® does not assume any liability for errors or inaccuracies.

691-176A February 2011

T E S E Q

Advanced Test Solutions for EMC