



MAIN FEATURES

- Built-in EFT / Burst generator module
- Built-in Micropulse generator module (ISO 7637, JASO, SAE and many more)
- Built-in coupling network 80 VDC, up to 200 A
- Built-in battery switch
- Overcurrent protection
- Front panel operation and remote control possible

UCS 200Nx.2 Series Ultra Compact Simulator

The UCS 200Nx.2 Ultra-Compact-Simulator series for automotive transients unifies the capabilities of an EFT/Burst simulator, a Micropulse simulator and the required coupling / decoupling network into one box. The UCS 200Nx.2 series is equipped to meet all international and most car manufacturer specifications from around the globe. The built-in coupling network ranges up to 200 A depending on the model and can be used and controlled by the LD 200N.

For tests beyond standard requirements the waveform parameters of the Micropulse generator can be varied in a wide range by using the so called FreeStyle mode.

Models

UCS 200N50.2	Built-in coupler 80 VDC / 50 A
UCS 200N100.2	Built-in coupler 80 VDC / 100 A
UCS 200N150.2	Built-in coupler 80 VDC / 150 A
UCS 200N200.2	Built-in coupler 80 VDC / 200 A

Technical Specification

Micropulse	
Amplitude	20 V ... 600 V +/- 10 % (depending on pulse)
Rise time	1 ... 10 µs +/- 50 % (depending on pulse)
Pulse width	50 ... 10'0000 µs +/- 10 % (depending on pulse)
Internal Resistance Ri	2 Ω, 4 Ω, 5 ... 100 Ω in 5 Ω steps, 200 Ω, 400 Ω, 450 Ω +/- 20 % (depending on pulse)
Polarity	pos / neg
Repetition rate	0.2 ... 999 s +/- 20 %
Battery switch off t2	40 µs ... 500 ms +/- 20 % (depending on pulse)
Battery off t3	< 100 us
Burstpulse	
Amplitude	25 ... 1000 V +/- 10 %
Rise time	5 ns +/- 30 %
Pulse width	150 ns +/- 30 %
Internal Resistance Ri	50 Ω +/- 20 %
Polarity	pos / neg
Burst duration (t4)	0.1 ... 999.9 ms
Repetition rate (t5)	10 ... 9'999 ms
Frequency (f)	0.1 ... 200 kHz
Test duration	1 s ... 9'900 h

Remark:

Not all above listed parameters for Micropulses are available for all the different pulses.

General Specifications

Parameter	UCS 200N50.2	UCS 200N100.2	UCS 200N150.2	UCS 200N200.2
Coupling network	80 VDC			
Coupling network	50 A continuous	100 A continuous	150 A continuous	200 A continuous
Inrush current	100 A @ 500 ms	150 A @ 500 ms	No	
Overcurrent protection	Yes			
Inputs	+/- VDS-IN +/- AUX-IN			
Outputs	+/- Test supply OUT Coaxial output for ISO 7637-3 testing			
Remote interfaces	GPIB / USB			
Other interfaces	D-sub connector, control for LD 200N			
Triggers	1 x Trigger OUT, 1 x Trigger IN			
Ext. impedance	YES, 10 Ω minimum setting at the generator + external impedance value (only for micro pulses)			
Safety	Safety circuit, Warning lamp			
Dimension	19" / 3 HU 449 x 154 x 557 mm	19" / 6 HU 449 x 287 x 557 mm	19" / 9 HU 449 x 420 x 557 mm	
Weigth	25 kg	29.2 kg	35.4 kg	
Power main supply	115 / 230 VAC +10/- 15 % ; 50 - 60 Hz			
Fusage	2 x 2 AT (230 VAC) / 2 x 4 AT (115 VAC)			
Temperature	10 ... 35 °C			
Humidity	30 ... 75 %, non condensing			
Athmospheric pressure	860 ... 1060 mbar			

Accessories

iso.control	Remote control software tool
ACC	Capacitive Coupling Clamp, for CCC testing acc. to ISO 7637-3
CA EFT kit	Calibration Adapter for Burst, consisting of 1 x 50 Ω / 1 x 1000 Ω matching resistor, 1 x adapter AD-CA EFT
CA ISO	Calibration Adapter, resistors for micro pulses acc. to ISO 7637-2 and load dump pulses acc to ISO 16750-2
AD-CA ISO	Adapter for CA ISO (only 150 A / 200A unit)
MSA 250-32	Adapter 150 A / 200A to 4 mm banana for AD-CA ISO and for pulse verification
AD-ISO-100A	Adapter 100 A to 32 A (4 mm banana)
CIP 9136A	Inductive Coupling Clamp, for ICC testing acc. to ISO 7637-3
MN-9136A	Matching network for CIP 9136A
PCJ 9201B	Calibration jig for CIP 9136A

More automotive emc test generators

AMP 200N2	Audio Amplifier Module for magnetic field and AC ripple testing
AutoWave	ArbWave generator but also much more
LD 200N series	Load dump transient generator
PFM 200N series	Power Fail Module for fast drop-out testing, rise time < 200 ns
PFS 200N series	Power Fail Simulator for dip and drop testing, rise time < 1 μs
VDS 200Qx.2 series	4-quadrant amplifier, -20 V ... + 80 VDC, up to 200 A

Pulses (extract)

ISO 7637-2	Pulse 1 (12 V)	Pulse 1 (24 V)	Pulse 2a (12 V / 24 V)
Amplitude	-75 ... -150 V +/- 10 %	-300 ... -600 V +/- 10%	+37 ... 112 V +/- 10%
Rise time	1 µs +/- 50 %	3 µs +/- 50 %	1 µs +/- 50 %
Pulse width	2 ms +/- 10 %	1 ms +/- 10 %	50 µs +/- 10 %
Int. resistor	10 Ω +/- 20 %	50 Ω +/- 20 %	2 Ω +/- 20 %

JASO D001	Pulse A2	Pulse B2	Pulse D2
Amplitude	+ 110 V +/- 10 %	-260 V +/- 10 %	+ 170 V +/- 10 %
Capacitor C	4.7 µF	33 µF	2.2 µF
Pulse width (tau)	2.5 µs	2 ms	2.5 µs
R1	0.6 Ω	60 Ω	1.2 Ω
R2	0.4 Ω	80 Ω	0.9 Ω

SAE J1455	Mutual	Inductive
Amplitude	+/- 300 V +/- 10 %	+/- 600 V +/- 10 %
Rise time	1 µs	1 µs
Pulse width	15 µs	1000 µs
Int. resistor	50 Ω	20 Ω

ISO 7637-1 (1990)	Pulse 6
Amplitude	- 300 V +/-10 %
Rise time	< 60 µs
Pulse width	300 µs +/- 10 %
Int. resistor	30 Ω +/-20 %

ISO 7637-2	Pulse 3a (12 V / 24 V)	Pulse 3b (12 V / 24 V)
Amplitude	- 112 ... -300 V +/- 10 %	75 ... 300 V +/-10 %
Rise time	5 µs +/- 30 %	5 µs +/- 30 %
Pulse width	150 µs +/- 30 %	150 µs +/- 30 %
Int. resistor	50 Ω +/- 10 %	50 Ω +/- 10 %